



Heavy-Duty Pumping, Zero Compromise.

EUFM OIL-FILLED PUMPSET



EUFM OIL-FILLED SUBMERSIBLE PUMPSET

technical data

Single Phase	0.5 HP to 3.0 HP, 240 V, 50Hz
Three Phase	1.0 HP to 7.50 HP, 415 V, 50Hz
Maximum Fluid Temperature	up to +90° C
Maximum Sand Content	0.25%
Pump size	3" & 4" Pumps and Motors

key advantages

Easy Maintenance and Rewinding

- Designed for effortless servicing, the pumps allow quick and convenient repairing and rewinding, reducing downtime and maintenance costs.

Available with Start Control Box or Digital Auto Control Box

- Each model is equipped with either a standard start control box or an advanced digital auto control box, ensuring seamless operation, enhanced protection, and user-friendly control.

Engineered with Casing-Stressed Design

- The pumps are developed using a casing-stressed construction, ensuring superior structural strength, higher pressure handling, and long-lasting durability.

Built to NEMA Dimension Standards

- Designed in accordance with NEMA dimensional specifications, these pumps ensure compatibility, interchangeability, and global standardization.

High Performance in Low Voltage Conditions

- The pumps deliver excellent water output even during low-voltage fluctuations, making them ideal for regions with unstable power supply.