



SHRIDEV



**Maximum Durability. Zero Blockage.**

**SEWAGE PUMPS**



# EUFM SEWAGE PUMPS

## technical data

|                             |                                                                                          |
|-----------------------------|------------------------------------------------------------------------------------------|
| Max. Liquid Temp.           | Up to +40°C                                                                              |
| Permissible pH Range        | 4 to 10                                                                                  |
| Max. Liquid Density         | $1.2 \times 10^3 \text{ kg/m}^3$                                                         |
| Power Frequency             | 50 Hz                                                                                    |
| Nominal Voltage             | Single Phase - 220 VAC<br>Three Phase - 380 VAC<br>Operating Voltage Range - 10% to +10% |
| Recommended Immersion Depth | 0.5 m to 5 m                                                                             |

## key advantages

### Robust All Cast-Iron Design

- Wear-resistant, corrosion-resistant, and engineered for extended durability with an aesthetically refined finish.

### Double Channel Impeller

- Ensures smooth solids handling capacity, improved discharge efficiency, and excellent hydraulic performance.

### Stainless Steel Shaft Extension

- Enhanced strength and corrosion resistance for improved reliability during prolonged operation.

### Advanced Double-Sided Carbide Mechanical Seal

- Offers superior sealing performance, reduced leakage, and longer service intervals even in abrasive sewage environments.